



RS-9 - RESIDENTIAL SINGLE-FAMILY DISTRICT

The RS-9, Residential Single-Family District is primarily intended to accommodate moderate to high density single-family detached dwellings in urban areas at a maximum overall density of 4.0 units per acre. Public water and public sewer service is required in this district.

Minimum Lot Size:	9,000 square feet
Minimum Lot Width:	
Interior:	60 feet
Corner:	75 feet
Minimum Street Frontage:	30 feet
Minimum Street Setback: a	30/55 feet Local, Subcollector, Collector - Front
	15/40 feet Local, Subcollector, Collector - Side
	40/75 feet Minor Thoroughfare
	50/95 feet Major Thoroughfare
Minimum Side Setback:	5 feet
Minimum Rear Setback:	25 feet
Maximum Building Height: b	50 feet
Maximum Building Coverage:	35 % of lot

- a - Setback from right-of-way or property line/setback from street centerline, whichever is greater.
- b - No more than three (3) full or partial stories entirely above grade.

Notes:

- 1 - A corner lot has two (2) street setbacks. The setback of lower setback category shall be considered the side street. If both streets are of the same setback category, the property owner shall designate the side street for his lot.
- 2 - A through lot has two (2) street setbacks but no rear setback.
- 3 - On a corner lot of record, the side street setback may be reduced, if necessary, to yield a buildable width equal to sixty (60) percent of the lot width.
- 4 - For any lot of record, the street setback and the rear setback may be reduced, if necessary, to yield a buildable depth equal to forty (40) percent of the lot depth. The rear setback shall be reduced first, but not below fifteen (15) feet and the street setback shall not be reduced by greater than ten (10) feet.